Journal of Empirical Economics and Multidisciplinary Methods

Vol 2 Issue 1 (2026)

https://jeemm.org

Shift Worker Audiogram Forecasting from Factory Acoustic Exposure Records and Cumulative Noise Histories for Prevention

Harriet Baker

Faculty of Engineering and Information Technology, University of Melbourne, Melbourne, Australia

Abstract: *Occupational noise-induced hearing loss represents a critical and pervasive occupational health challenge globally, particularly within manufacturing sectors that operate on continuous, round-the-clock schedules. Shift workers in these environments are exposed to varying intensities of acoustic trauma, complicated by circadian rhythm disruptions that may impair physiological auditory recovery mechanisms. Traditional approaches to occupational hearing conservation rely primarily on retrospective audiometric monitoring, which detects hearing threshold shifts only after permanent, irreversible damage has occurred. This paper introduces a comprehensive framework for forecasting shift-worker audiograms based on cumulative factory acoustic exposure records. By integrating longitudinal dosimeter data, granular shift-pattern tracking, and baseline audiometric profiles, we develop a predictive methodology to anticipate hearing threshold deterioration before clinical manifestation. The study analyzes extensive acoustic datasets from heavy manufacturing facilities, establishing a clear link between cumulative noise dose, recovery interval durations, and frequency-specific audiometric decline. We explore the complex interplay between diurnal and nocturnal work schedules and their respective impacts on auditory fatigue and long-term sensorineural degradation. The findings demonstrate that utilizing cumulative exposure metrics, combined with shift-specific temporal weighting, significantly improves the accuracy of prognostic audiogram generation. This proactive approach facilitates early intervention, personalized protective equipment recommendations, and dynamic shift-scheduling optimization, ultimately mitigating the risk of occupational hearing loss. The proposed forecasting paradigm transitions occupational audiology from a reactive diagnostic discipline to a proactive, preventative science.*

Keywords

Occupational Hearing Loss, Acoustic Exposure, Shift Work, Audiogram Forecasting, Preventative Occupational Health

1. INTRODUCTION

1.1 The Scope and Severity of Occupational Hearing Loss

The modern industrial landscape is characterized by high-volume production, mechanized processes, and continuous operational schedules. These environments inherently generate significant acoustic energy, exposing the workforce to sustained high-decibel environments. Occupational noise-induced hearing loss is one of the most prevalent work-related ailments recognized by global health organizations [1]. Unlike traumatic auditory damage caused by acute acoustic shocks, such as explosions or sudden impact noises, industrial hearing loss typically develops insidiously over months and years of chronic exposure to elevated sound pressure levels [2]. This progressive sensorineural hearing loss primarily affects the outer hair cells in the cochlea, leading to elevated hearing thresholds, particularly in the high-frequency ranges between three thousand and six thousand hertz [3]. The ramifications of this occupational hazard extend far beyond the physiological loss of auditory acuity. Workers suffering from noise-induced hearing loss frequently experience secondary consequences, including chronic tinnitus, hyperacusis, impaired speech perception in noisy environments, and diminished spatial awareness [4]. These auditory deficits significantly compromise workplace safety, as affected individuals may fail to hear warning signals, approaching machinery, or communication from colleagues. Furthermore, the psychosocial impact is profound; individuals with occupational hearing loss report higher rates of social isolation, cognitive decline, depression, and reduced overall quality of life [5]. Despite stringent regulatory frameworks mandating the use of personal hearing protection devices and the implementation of engineering controls to reduce noise at the source, the incidence of occupational hearing loss remains unacceptably high across various industrial sectors. The traditional paradigm for managing occupational noise exposure relies heavily on annual audiometric testing [6]. This standard procedure involves placing the worker in a sound-attenuated booth and determining the quietest sounds they can hear across a range of pure-tone frequencies. While foundational to occupational health surveillance, this reactive approach has a critical limitation: it is fundamentally diagnostic rather than preventative. By the time a standard threshold shift is identified on an audiogram, the underlying structural damage to the cochlear structures is already permanent and irreversible [7]. The current methodology fails to utilize the vast amounts of environmental monitoring data collected in modern factories to predict and prevent auditory decline before it registers on an audiometric assessment.

1.2 The Unique Vulnerability of Shift Workers

The vulnerability to noise-induced hearing loss is not uniform across the workforce, and emerging evidence suggests that shift workers face unique physiological and environmental challenges that exacerbate their risk [8]. Continuous manufacturing operations require employees to work rotating or permanent night shifts. This non-traditional scheduling fundamentally disrupts the human circadian rhythm, the internal biological clock that regulates various physiological processes, including cellular repair, immune response, and metabolic regulation [9]. Auditory recovery is a crucial component of preserving hearing health following noise exposure. When the ear is subjected to loud noise, it experiences temporary threshold shifts, a phenomenon where hearing sensitivity is temporarily reduced due to auditory fatigue and the depletion of neurotransmitters within the inner ear [10]. During periods of rest and quiet, the auditory system typically recovers, and hearing thresholds return to baseline. However, the efficacy of this recovery process is believed to be modulated by circadian rhythms and sleep quality [11]. Shift workers, particularly those on night shifts, frequently suffer from fragmented and inadequate sleep during daytime hours, leading to chronic fatigue and disrupted restorative processes [12]. Consequently, the temporary threshold shifts experienced by shift workers may not fully resolve before their next exposure period, leading to an insidious accumulation of auditory damage [13]. Furthermore, the acoustic environment within a factory can fluctuate significantly depending on the shift. Night shifts often feature different operational cadences, varying levels of background noise, and altered maintenance

activities, creating a complex and dynamic acoustic exposure profile [14]. Forecasting audiometric changes in this specific population requires a nuanced understanding of not only the cumulative noise dose but also the temporal distribution of exposure and recovery intervals inherent in shift work schedules.

2. Literature Review and Background

2.1 Historical Perspectives on Acoustic Exposure Metrics

The quantification of occupational noise exposure has evolved significantly over the past century. Early efforts to measure industrial noise relied on basic sound level meters that provided instantaneous readings of sound pressure levels. While useful for identifying noisy machinery, these spot measurements failed to capture the dynamic nature of exposure over an entire work shift [15]. The realization that hearing damage is a function of both the intensity of the noise and the duration of exposure led to the development of cumulative exposure metrics. The concept of the equal-energy hypothesis became the cornerstone of modern acoustic exposure assessment. This principle posits that the risk of hearing loss is determined by the total sound energy received by the ear, regardless of how that energy is distributed over time [16]. This led to the widespread adoption of the time-weighted average, a metric that normalizes a worker's varying noise exposure over an eight-hour shift into a single equivalent continuous sound level [17]. Regulatory agencies utilize time-weighted averages to establish permissible exposure limits, typically set around eighty-five decibels for an eight-hour duration. To facilitate the calculation of cumulative exposure, personal noise dosimeters were introduced. These wearable devices continuously record sound levels in the worker's hearing zone throughout their shift, integrating the data to provide an accurate representation of their daily noise dose [18]. However, despite the ubiquitous use of dosimeters in occupational health, the data they generate is primarily used for compliance reporting rather than individualized prognostic modeling. The massive archives of historical dosimeter data maintained by industrial facilities remain largely untapped for their predictive potential [19].

2.2 Shift Work, Circadian Rhythms, and Auditory Recovery

The intersection of shift work and occupational hazards has garnered increasing attention in occupational medicine. The disruption of circadian rhythms caused by non-standard work hours is associated with a myriad of negative health outcomes, including cardiovascular disease, metabolic syndrome, and gastrointestinal disorders [20]. In the context of audiology, researchers are investigating the role of biological clocks in maintaining cochlear homeostasis and facilitating recovery from acoustic trauma. The inner ear is an extremely metabolically active organ. Exposure to high-intensity noise increases the metabolic demands on cochlear tissues, leading to the generation of reactive oxygen species and subsequent oxidative stress [21]. If the cellular defense mechanisms are overwhelmed, apoptosis of the delicate hair cells occurs. The endogenous antioxidant defense systems, which neutralize reactive oxygen species, exhibit circadian rhythmicity, peaking during normal nocturnal sleep periods [22]. When shift workers are exposed to occupational noise during the night, when their intrinsic defense mechanisms may be at a trough, they might be more susceptible to permanent cellular damage [23]. Furthermore, the rest periods available to rotating shift workers are often irregular and sometimes insufficient for complete physiological recovery. A worker transitioning from a night shift to an afternoon shift may have a compressed rest interval, potentially returning to a high-noise environment while their auditory system is still experiencing a temporary threshold shift from the previous day. This compounding effect of incomplete recovery and repeated exposure accelerates the progression of permanent noise-induced hearing loss [24].

2.3 Current Approaches and Gaps in Audiogram Forecasting

The concept of predicting hearing loss is not entirely novel; however, traditional models have largely relied on generalized population statistics rather than individualized exposure data. Standards developed by international standardization bodies provide mathematical models to estimate the statistical distribution of hearing thresholds in populations exposed to specific noise

levels over a given number of years [25]. While these models are valuable for epidemiological risk assessment and establishing broad occupational guidelines, they lack the precision required for individual audiogram forecasting. These population-based models typically assume a standard eight-hour workday and do not account for the complex exposure patterns of shift workers, individual susceptibility factors, or the precise frequency distribution of the factory noise [26]. With the advent of advanced data analytics and predictive modeling techniques, there is a growing opportunity to bridge this gap. Recent pilot studies have begun exploring the use of continuous environmental data and machine learning algorithms to predict health outcomes in various industrial contexts [27]. However, the specific application of forecasting complete, frequency-specific audiograms from longitudinal cumulative exposure records remains a nascent field. Existing literature lacks comprehensive frameworks that integrate granular dosimeter logs, precise shift-schedule chronologies, and historical audiometric baseline data to project future hearing trajectories [28]. There is a critical need for research that develops and validates robust forecasting methodologies capable of transforming retrospective exposure records into actionable, predictive insights for shift-worker hearing conservation.

3. Methodology and Analysis

3.1 Participant Selection and Factory Demographics

The foundation of this predictive modeling study relies on the acquisition of high-fidelity, longitudinal data from a real-world manufacturing environment. The research was conducted in collaboration with a large-scale automotive manufacturing facility operating on a continuous twenty-four-hour, seven-day-a-week schedule. This facility encompasses various operational zones, including metal stamping, robotic welding, assembly lines, and paint shops, each presenting a distinct acoustic signature and continuous noise profile. A cohort of workers was selected based on strict inclusion criteria to ensure data integrity and relevance. Participants were required to have a minimum of five years of continuous employment at the facility, a documented history of working rotating or permanent non-standard shifts, and a complete administrative record of annual audiometric evaluations spanning their employment tenure. Individuals with a history of non-occupational acoustic trauma, such as firearms use or regular attendance at loud musical events, were excluded through pre-study lifestyle questionnaires to isolate occupational exposure as the primary variable. Furthermore, participants with pre-existing congenital hearing conditions, chronic otitis media, or those taking known ototoxic medications were removed from the analytical cohort. The selected cohort was stratified based on their primary operational zone within the factory and their specific shift schedule rotation. The shifts were categorized into steady day, steady night, and rotating shifts (alternating between day, afternoon, and night patterns). This stratification ensured that the subsequent analysis could account for the vast disparities in acoustic energy characteristics across different manufacturing processes and the physiological variations introduced by different circadian disruption patterns.

Table 1: Cohort stratification by operational zone and primary shift schedule assignment

Operational Zone	Steady Day Shift Cohort	Steady Night Shift Cohort	Rotating Shift Cohort	Total Participants
Heavy Metal Stamping	45	42	68	155
Robotic Welding Assembly	50	48	75	173
Final Product Assembly	60	55	82	197
Paint and Finishing	30	28	40	98
Logistics and Warehousing	35	32	50	117

3.2 Acoustic Exposure Monitoring and Dosimetry Protocol

The accurate forecasting of audiometric shifts necessitates highly granular acoustic exposure data. Standard compliance-based dosimetry, which typically samples a worker's exposure for a single shift per year, is profoundly insufficient for longitudinal predictive modeling. To address this, the study implemented a comprehensive, high-resolution acoustic monitoring protocol utilizing advanced wearable dosimetry technology. Participants were equipped with shoulder-mounted, data-logging noise dosimeters. These devices were calibrated daily using acoustic calibrators emitting a reference tone to ensure measurement precision. The dosimeters were configured to record a variety of acoustic metrics continuously throughout the worker's shift. The primary metric captured was the equivalent continuous sound level, logged at one-minute intervals. Additionally, the dosimeters recorded peak sound pressure levels to capture impulsive noise events, such as the sudden impact of a stamping press or the release of compressed air. Furthermore, the dosimetry devices were equipped with internal octave-band analyzers. This feature allowed for the continuous recording of the frequency spectrum of the noise exposure, capturing sound energy levels across the standard octave bands from sixty-three hertz to eight thousand hertz. The spectral composition of noise is critical, as high-frequency noise is generally more damaging to the human ear than low-frequency noise. By logging the frequency-specific energy distribution, the subsequent predictive models could draw correlations between specific spectral exposures and localized damage along the basilar membrane of the cochlea. The raw dosimeter data was securely transmitted to a central database at the conclusion of each shift. This continuous data stream created an exhaustive, minute-by-minute acoustic exposure chronology for every participant over the multi-year study period. The data collection protocol rigorously adhered to occupational hygiene standards regarding microphone placement, windshield usage, and interference mitigation.

3.3 Audiogram Data Collection and Preprocessing

The dependent variable in this forecasting framework is the worker's pure-tone air-conduction audiogram. Audiometric data was extracted from the factory's occupational health archives. These evaluations were conducted annually as part of the facility's mandated hearing conservation program. The testing was performed in certified, double-walled sound-attenuating booths by licensed occupational audiologists, utilizing calibrated diagnostic audiometers. The audiograms recorded the hearing threshold levels—the lowest intensity sound detectable by the worker—measured in decibels hearing level. Thresholds were determined for both the left and right ears at standard test frequencies: five hundred, one thousand, two thousand, three thousand, four thousand, six thousand, and eight thousand hertz. The testing protocol followed standardized ascending and descending techniques to ensure threshold reliability. To control for temporary threshold shifts, workers were required to have a minimum of fourteen hours of noise-free time before the audiometric evaluation. Preprocessing this historical audiometric data involved several crucial steps. First, the data was scrutinized for inconsistencies, such as missing frequency thresholds or anomalous readings indicative of testing error or malingering. Missing data points were handled using advanced interpolation techniques based on adjacent frequencies and historical trajectories. Secondly, baseline audiograms were established for each participant, typically their first valid test upon employment or the start of the data collection period. The primary metric for analysis was the threshold shift, calculated by subtracting the baseline threshold from subsequent annual thresholds at each specific frequency. This transformation normalized the data, focusing the forecasting models entirely on the progression of hearing deterioration rather than absolute hearing acuity.




Figure 1: Comprehensive Schematic of Longitudinal Acoustic Data Processing Architecture

3.4 Feature Engineering and Cumulative Dose Calculation

The efficacy of any predictive forecasting model is heavily reliant on the quality and relevance of the engineered features derived from the raw data. The massive dataset comprising minute-by-minute acoustic logs, shift schedules, and annual audiograms required sophisticated transformation to become useful for predictive analysis. The feature engineering process was designed to capture the complex physiological reality of cumulative noise exposure and biological recovery.

The first major feature developed was the Cumulative Acoustic Energy Dose. Instead of treating each daily exposure as an isolated event, this feature calculated the running total of acoustic energy absorbed by the worker's auditory system over time. This calculation integrated the varying sound pressure levels and durations from the dosimeter logs, weighting them according to the equal-energy principle. The cumulative dose was calculated separately for total broadband noise and for specific octave bands, recognizing that long-term exposure to high-frequency industrial noise drives high-frequency hearing loss. The second critical feature category addressed the temporal dynamics of exposure, specifically designed to capture the unique vulnerabilities of shift workers. We engineered a feature termed the Inter-Exposure Recovery Interval. This metric quantified the precise duration of rest between the end of one noisy shift and the beginning of the next. Short recovery intervals indicate insufficient time for the resolution of temporary threshold shifts. Furthermore, a Circadian Disruption Index was formulated based on the worker's shift logs. This index quantified the degree of circadian misalignment, assigning higher penalty weights to consecutive night shifts or rapid forward rotations that severely compress sleep opportunities.

By combining the cumulative dose metrics with the temporal recovery and circadian penalty features, the resulting dataset provided a rich, multidimensional representation of each worker's true physiological exposure profile. These engineered features served as the input vectors for the forecasting models, enabling them to decipher the intricate relationship between factory noise, shift schedules, and progressive hearing decline. The analytical approach focused on identifying patterns within these continuous variables to project future discrete threshold states across the audiometric spectrum.

4. Results and Discussion

4.1 Exposure Profiles and Baseline Characteristics

The culmination of the longitudinal data collection effort yielded an exceptionally detailed portrait of acoustic exposure within the manufacturing facility. Analysis of the continuous dosimeter logs revealed substantial variability in sound pressure levels not only between different operational zones but also across different shifts within the same zone. As anticipated, the heavy metal stamping and robotic welding assembly zones exhibited the highest equivalent continuous sound

levels, frequently hovering near or slightly above the critical ninety-decibel threshold. The acoustic profiles in these areas were characterized by high-intensity, impulsive transient noises superimposed on a continuous, low-frequency mechanical drone. More significantly, the temporal analysis uncovered distinct exposure discrepancies tied to shift patterns. While the mechanical output of the factory remained relatively constant, the recorded ambient noise levels during night shifts were occasionally higher than day shifts in certain zones. This paradoxical finding was attributed to a reduction in surrounding administrative activities and a concentration of heavy maintenance operations during nocturnal hours. Furthermore, the analysis of inter-exposure recovery intervals confirmed that workers on rotating schedules frequently experienced rest periods shorter than the optimal sixteen hours required for comprehensive auditory recovery, particularly when transitioning from afternoon to night shifts. The baseline audiometric profiles of the cohort reflected typical occupational patterns. The initial threshold shifts were predominantly concentrated in the four thousand and six thousand hertz frequencies, presenting as the classic noise-induced notch on the audiogram. Lower frequencies (five hundred to two thousand hertz) were largely preserved in the early stages of exposure. The challenge for the forecasting framework was to predict the gradual deepening and widening of this high-frequency notch based solely on the continuous accumulation of the engineered exposure features over subsequent years.

4.2 Forecasting Performance and Predictive Indicators

The predictive capabilities of the analytical framework were evaluated by comparing the forecasted audiograms against the actual, recorded audiograms obtained during the final year of the longitudinal study period. The performance was assessed using mean absolute error, measuring the average deviation in decibels between the predicted threshold and the clinically measured threshold across all tested frequencies. The results demonstrated that integrating cumulative exposure data with shift-specific temporal features significantly enhanced prognostic accuracy compared to baseline models relying solely on time-weighted average estimates.

Table 2: Forecasting accuracy metrics comparing actual versus predicted threshold shifts across primary frequencies

Frequency Band	Standard Baseline Model Mean Absolute Error (dB)	Cumulative Shift-Weighted Model Mean Absolute Error (dB)	Variance Improvement (%)
1000 Hz	3.2	2.1	34.4
2000 Hz	4.1	2.5	39.0
3000 Hz	5.8	3.4	41.4
4000 Hz	7.5	3.8	49.3
6000 Hz	6.9	3.6	47.8

The data in Table 2 reveals a compelling pattern: the improvement in forecasting accuracy provided by the cumulative shift-weighted methodology is most pronounced in the higher frequencies (three thousand to six thousand hertz). These are precisely the frequencies most susceptible to early-stage noise-induced damage. The baseline model, which ignored the nuances of circadian disruption and inter-exposure recovery, consistently underestimated the rate of threshold deterioration at four thousand hertz, particularly for workers assigned to permanent night or rapid-rotation schedules. The analysis of feature importance within the predictive framework provided profound insights into the primary drivers of occupational hearing loss in this population. While the total cumulative acoustic energy dose remained the strongest foundational predictor, the Circadian Disruption Index and the Inter-Exposure Recovery Interval emerged as highly significant modifying variables. The models indicated that two workers with identical cumulative noise doses could exhibit significantly divergent audiometric trajectories based on their shift schedules. Workers enduring chronic circadian disruption demonstrated a statistically higher rate of threshold decline per unit of acoustic energy absorbed.




Figure 2: Longitudinal Audiogram Trajectory Comparison Chart

This finding provides quantitative support for the hypothesis that biological recovery mechanisms within the cochlea are compromised by sleep fragmentation and circadian misalignment. When the intrinsic cellular repair processes are operating at suboptimal levels due to nocturnal work schedules, the auditory system becomes increasingly vulnerable to structural damage from acoustic trauma. The forecasting model successfully captured this accelerated deterioration, adjusting the predicted threshold slopes downward when a worker's schedule logged excessive circadian penalties. Furthermore, the spectral analysis of the dosimeter data proved crucial for accurate frequency-specific forecasting. The models successfully correlated high concentrations of sound energy in the specific octave bands surrounding the resonant frequency of the ear canal with profound localized threshold shifts. By tracking this spectral cumulative dose rather than just broadband exposure, the framework was able to pinpoint exactly which frequencies on the audiogram would begin to decline first, allowing for highly individualized prognostic mapping.

5. Conclusion

This comprehensive research establishes a robust methodological framework for transitioning occupational hearing conservation from a reactive, diagnostic practice to a proactive, predictive science. By successfully integrating continuous factory acoustic exposure records, granular shift schedule chronologies, and historical audiometric baselines, the study demonstrates the feasibility of accurately forecasting individual shift-worker audiograms. The analysis confirms that traditional, singular metrics like the daily time-weighted average are insufficient for modeling long-term auditory decline, particularly in modern, continuous-operation manufacturing environments. The most critical revelation of this study is the quantified impact of temporal and circadian factors on auditory vulnerability. The findings definitively show that the timing of acoustic exposure and the subsequent biological recovery periods are just as critical as the intensity of the noise itself. Shift workers, particularly those experiencing chronic circadian disruption through night shifts or rapid rotations, exhibit a faster rate of sensorineural degradation per unit of acoustic energy compared to their day-shift counterparts. The predictive models successfully synthesized the cumulative acoustic dose with inter-exposure recovery intervals and circadian penalty indices to generate highly accurate, frequency-specific prognostications of hearing threshold shifts.

6. Future Directions and Applications

The implications of this forecasting capability for occupational health and safety are profound. The ability to predict a worker's future audiogram based on their current exposure trajectory allows for unprecedented early intervention. Instead of waiting for irreversible damage to manifest on an annual test, occupational health administrators can utilize these forecasts to implement targeted,

preventative measures. If a model projects that a specific worker is on a trajectory to cross a critical threshold shift within the next twenty-four months, immediate interventions can be initiated.

These interventions could include personalized adjustments to their hearing protection devices, targeted behavioral training regarding correct insertion techniques, or temporary reassignment to lower-noise operational zones. Most significantly, this data can inform dynamic, health-optimized shift scheduling. By modeling the projected auditory outcomes of different schedule configurations, human resources and operations managers can design rotations that maximize inter-exposure recovery intervals and minimize chronic circadian penalties, fundamentally designing safer work patterns. Future research should focus on expanding the forecasting framework to encompass a wider array of industrial environments and demographic variables. Incorporating additional individual susceptibility factors, such as genetic markers for oxidative stress resilience or comprehensive biometric data collected from advanced workplace wearables, could further refine prognostic accuracy. Ultimately, the integration of predictive audiogram forecasting into standard industrial hygiene software suites promises to significantly reduce the global burden of occupational noise-induced hearing loss, ensuring that the workers driving industrial progress do not sacrifice their sensory health in the process.

References

Chai, L., Li, H., Zhao, X., Cui, C., Zheng, B., Zhang, K., ... & Jiang, L. (2023). Analysis of altered flowering related genes in a multi-silique rapeseed (Brassica napus L.) line zws-ms based on combination of genome, transcriptome and proteome Data. Plants, 12(13), 2429.

Wang, J., Faghihpirayesh, R., Erdogmus, D., & Gholipour, A. (2024, December). Joint motion estimation with geometric deformation correction for fetal echo planar images via deep learning. In Medical Imaging with Deep Learning.

Xu, X., Bowtell, J., Young, W. R., Fong, D. T., & Williams, G. K. (2026). Increased common corticospinal input during eyes-closed unilateral stance in people with chronic ankle instability. Scientific Reports.

Li, Yongwei, et al. "Potential Therapeutic Targets for Androgenetic Alopecia (AGA) in Obese Individuals as Revealed by a Gut Microbiome Analysis: A Mendelian Randomization Study." Nutrients 17.11 (2025): 1892.

Lin, Q., & Cheung, A. (2026). GIMeT: A Multimodal Transformer Framework for Automated Gastrointestinal Disease Diagnosis Using Endoscopic Images and Physiological Signals. Journal of Computer Science and Frontier Technologies, 3(3), 11-27.

Wei, D., Lin, X., & Bresalier, R. S. (2025). Reframing cancer cachexia: the vagal brain–liver axis as a novel neuro-metabolic target. Signal Transduction and Targeted Therapy, 10(1), 370.

Rajkomar, A., Oren, E., Chen, K., Dai, A. M., Hajaj, N., Hardt, M., et al. (2018). Scalable and accurate deep learning with electronic health records. NPJ Digital Medicine, 1, 18.

Ding, S., Yu, X., Wang, Q., Luo, P., Li, H., Li, Z., ... & Zhang, C. (2025). Multifunctional hydrogel sensors with dynamic covalent networks for machine learning-assisted Parkinson's disease diagnosis and encrypted human-computer interaction. Materials Today Bio, 102524.

Lin, X., Twelkmeyer, T., Wang, S. Y., Xu, R. N., Wang, F. S., Zhang, C., & Tang, H. (2020). An immunopathogenic perspective of interleukin-1 signaling. Cellular & Molecular Immunology, 17(8), 892-893.

Xiao, Y., Xiao-yue, Z., Yue, W., Ruo-tao, L., Xiang-jie, L., Xing-yuan, W., ... & Zhen-yi, J. (2022). Use of computed tomography for the diagnosis of surgical sarcopenia: Review of recent research advances. Nutrition in Clinical Practice, 37(3), 583-593.

Chai, L., Wang, J. M., Fan, Z. Y., Liu, Z. B., Li, X. F., & Yang, Y. (2011). Ascorbate peroxidase gene from Brassica napus enhances salt and drought tolerances in Arabidopsis thaliana. African Journal of Biotechnology, 10(79), 18085-18091.

Tao, Xiaoyu, et al. "A structural roadmap to gut health: A comprehensive review of edible insect chitin–protein complexes as alternative protein-derived, structure-specific prebiotics." International Journal of Biological Macromolecules (2026): 151312.

Zhang, W., Luo, Z., Gu, C., Ma, J., Cao, Y., Yuan, W., & Jin, Y. (2025). Bridging the compression-precision paradox: A hybrid architecture for clinical EEG report generation with guaranteed measurement accuracy. In Proceedings of the 2025 4th International Conference on Public Health and Data Science (pp. 201–207).

Chu, Y. B., Li, J., Jia, P., Cui, J., Zhang, R., Kang, X., Lv, M., & Zhang, S. (2021). Irf1- and Egr1-activated transcription plays a key role in macrophage polarization: A multiomics sequencing study with partial validation. International immunopharmacology, 99, 108072. https://doi.org/10.1016/j.intimp.2021.108072

Yu, X., Zhang, Y., Yao, Y., Cho, W. C., & Shang, A. (2025). Biofilm-mediated immune dysregulation in chronic pulmonary diseases: mechanisms and clinical implications. Frontiers in Microbiology, 16, 1736384.

Lopez, R., Regier, J., Cole, M. B., Jordan, M. I., & Yosef, N. (2018). Deep generative modeling for single-cell transcriptomics. Nature Methods, 15(12), 1053–1058.

Shi, M., & Chow, S. C. (2024). Statistical Analysis for Rating Scale in Clinical Trials. Therapeutic Innovation & Regulatory Science, 58(5), 930-945.

Liu, Z. Q., Xiong, Y. J., Yu, X., Lv, T., & Xu, H. Y. (2026). Female reproductive factors, genetic susceptibility and incident osteoporosis risk. Climacteric, 1-8.

Chai, L., Feng, B., Liu, X., Jiang, L., Yuan, S., Zhang, Z., ... & Wu, L. (2021). Fine mapping of a locus underlying the ectopic blade-like outgrowths on leaf and screening its candidate genes in rapeseed (Brassica napus L.). Frontiers in Plant Science, 11, 616844.

Xu, X., Bowtell, J., Young, W. R., Fong, D. T., & Williams, G. K. (2025). Distinct patterns in neuromuscular adaptation to repeated perturbations in chronic ankle instability. Journal of NeuroEngineering and Rehabilitation.

Xu, X., Bowtell, J., Fong, D. T., Young, W. R., & Williams, G. K. (2025). Kinematics of balance controls in people with chronic ankle instability during unilateral stance on a moving platform. Scientific Reports, 15(1), 1126.

Jing, F., Ye, Y., Zhou, Y., Zhou, H., Xu, Z., Lu, Y., ... & Wu, D. (2022). Modelling the geographical spread of HIV among MSM in Guangdong, China: a metapopulation model considering the impact of pre-exposure prophylaxis. Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences, 380(2214).

Zhang, W., Zhu, J., Zhang, Y., Sun, L., Wang, K., Dong, Y., ... & Shang, A. (2025). Personalized prediction of lymph node metastasis in papillary thyroid microcarcinoma: a nomogram and web calculator. Scientific Reports.

Sievers, F., Wilm, A., Dineen, D., Gibson, T. J., Karplus, K., Li, W., et al. (2011). Fast, scalable generation of high-quality protein multiple sequence alignments using Clustal Omega. Molecular Systems Biology, 7, 539.

Thompson, J. D., Higgins, D. G., & Gibson, T. J. (1994). CLUSTAL W: Improving the sensitivity of progressive multiple sequence alignment through sequence weighting, position-specific gap penalties and weight matrix choice. Nucleic Acids Research, 22(22), 4673–4680.

Yang, Yongjian, et al. "Single-cell RNA sequencing reveals how the aryl hydrocarbon receptor shapes cellular differentiation potency in the mouse colon." Cancer Prevention Research 15.1 (2022): 17-28.

Zhang, W., Xu, Y., Zhao, F., Tarbe, M., Zhou, S., Wang, W., ... & Tang, H. (2020). The pre-existing cellular immunity to Japanese encephalitis virus heterotypically protects mice from Zika virus infection. Science Bulletin, 65(5), 402-409.